



Douglas® VCP-MAX Windscreen (Vinyl Coated Polyester Fabric)

6' H - Dark Green ITEM # 21640, Black ITEM # 21642, Open Blue ITEM # 21644
9' H with TAB - Dark Green ITEM # 21940T, Black ITEM # 21942T, Open Blue ITEM # 21944T



Black



Dark Green



Open Blue

VCP Max goes one step further by offering maximum tensile strength and visual blockage. At 85% windbreak, VCP Max allows more airflow than closed mesh screens, but provides a better visual background than open mesh screens. This versatile and attractive windscreen fabric is durable and boasts great weather resistance. Custom digital printing and logos can be printed directly on the material. Screen length is completely custom and made to order to the nearest inch; 60 ft is the maximum recommended length per panel.

SPECIFICATIONS

FABRIC: 16 x 17 weave

WINDBREAK: 85%

WEIGHT PER SQUARE YARD: 10 oz.

TENSILE STRENGTH: 395 x 401

WARRANTY: 4 Year Limited

STANDARD COLORS: Dark Green, Black, or Open Blue.



HEMS

VCP windscreen material is hemmed with Douglas's 3-ply extra-strong hems. These durable hems are seamed with solid vinyl inserts that are double sewn to 1-1/2 inches wide. The #2 brass grommets are spaced every 12 inches on panel sides and every 18 inches along the top and bottom.

REINFORCEMENT

When installing windscreens, center reinforcement is recommended for anti-billowing on all panels that are taller than 6 ft and where strong winds prevail. Center reinforcement allows the screen to be secured to the middle of the fence with tie wraps or lacing cord attachment. All Sport Screens by Douglas® over 6 ft in height include a center tab with grommets. Center tabs on Vinyl Coated Polyester are sewn with 18 oz black vinyl and grommets are placed every 18 inches to secure the screen to the fence. The reinforcement tab is only visible on the backside of the fence screen for a cleaner installed appearance.



Center Reinforcement TAB



Die Cut Air Vents



Reinforced Air Vents



Full Color Digital Printing

AIR VENTS

Optional air vents allow air to pass through and help take the strain off your fence and windscreen. Air vents are recommended for screens taller than 6 ft and where high winds prevail. Standard air vents are a die-cut and heat sealed in a half moon shape. Air vents measure 8 inches wide and are 5 inches high and are cut out on 10 ft intervals. The Douglas® AVR vents are rectangular sewn cut outs that measure 8 inches wide by 10 inches high. These vents are perimeter hemmed with polyester webbing and are placed at 10 ft intervals on center.

PRINTING

Adding fence screen to bare fences around a facility, stadium or construction site is a huge branding and advertising opportunity. Boring chain link fences and bleachers can become billboards by adding full color digital graphics. Our elite printing process allows us to print directly on the material so there's no white back side like other digital printing companies. With the use of quality long lasting UV inks, your printing and logos become part of the material.

1-800-553-8907
douglas-sports.com